

MS-UNIBLACK INSTRUCTIONS



oliser

Mesrutiyet caddesi. Hatay Sokak. 17/B
06640. Kızılca / Ankara
Turkey

Tel : +90 312 417 72 75

Fax : +90 312 425 72 81

Web : www.oliser.com.tr

Email : oliser@oliser.com.tr



preparation

Place an Ink supply bottle to the back of the machine and insert the ink supply tube into the bottle. Insert the compressed air output (must be adjusted max. 8 Bars/90PSI) via Air In connector 6mm diameter size.

Plug in the plug and the machine will be ready to start filling .

Now, The machine is ready to fill the cartridges. Before filling the cartridges, be sure that they are empty. If not, evacuate the remaining ink from cartridge.

Strictly recommended : Before filling the cartridges we recommend you to clean the printheads of the cartridges by a steam generator. It will help you to fill the cartridges easily and will open the all clogged or dried printheads, So, your success rate will increase

INSTALLATION



Pressure Regulator will be shipped you separately , so first you will install it the place of it as shown above left side of the machine. Two screws are provided for the installation of pressure regulator , screw them together with the pressure regulator and fix it on the left side of the machine, connect the inlet tube to the pressure regulator and connect compressed air tube (6mm) to the pressure regulator as shown shown right.




FILLING



Insert the cartridge into the cradle , connect the filling tube. Place the cradle on the machine.


HP 15/45 and HP 26/29/14 cartridges printhead in up position. (all other cartridges printhead will be down position)



Push the Start/Stop Button.



CLEANING & EVACUATION



Insert the cartridge into the cradle , connect the cleaning&evacuation tube. Place the cradle on the machine.

All Cartridges must be cleaned and evacuated through and from the printhead.



Cartridge	Filling Time	Pressure Time	Empty	Full
51626a	2,40	9	20gr	60gr
51629a	2,40	9	20gr	60gr
c6614a	2,40	9	20gr	60gr
51645a	2,20	7	68gr	110gr
c6615a	2,20	7	68gr	110gr
c8727a	0,55	4	28gr	43gr
c6656a	1,05	4	28gr	47gr
10N0016	1,05	4	18gr	36gr
13400/17G0050	1,20	4	30gr	65gr

Available Cradles

HP - 51626A / 51629A / C6614A / 51633

HP - 51645 / C6615

HP - C8727 / C6656

Lexmark 13400HC Series

Lexmark 12A1970 Series

Lexmark 10N Series

Tube replacement of motors

